

LIGHT

LG-05

LECTRONICS Co.

4D94C-00

DATA SHEET

SPEC. NO. : SZ210  
DATE : 2022/13  
REV. : A/3 2

Approved By: [Signature]

By: [Signature]

Ver

Change History

REV.	
A/0	
A/1	Pin and PCB surface improved
A/2	Pin and PCB surface
A/3	In order to improve the product at the client, the modified from "0.05 technical and

Content)

The problem of wa  
ing the colloid size  
s are modified from  
0.05".

out affecting the ass  
ng of the pin and PCB s  
0±0.1" after negotia  
rtment of both part

Part No. LG-05IR4D94C-



## Absolute Maximum Ratings at Ta=25°C

Parameter	MAX.	Unit
Power Dissipation	200	mW
Continuous Forward Current	100	mA
Peak Forward Current*3	200	mA
Reverse Voltage	5	V
Operating Temperature	-40 to + 85	
Storage Temperature	-40 to + 100	
IR Reflow Temperature	245 for 30 seconds	

### 1. Storage

The storage ambient for the LEDs should not exceed 30°C temperature or 70% relative humidity.

It is recommended that LEDs out of their original packaging are used within three months.

For extended storage out of their original packaging, it is recommended that the LEDs be stored in a sealed container with appropriate desiccant or in desiccators with nitrogen ambient.

### 2. Precautions in handling:

- When soldering, leave 2mm of minimum clearance from the resin to the soldering point.
- Dipping the resin to solder must be avoided.
- Correcting the soldered position after soldering must be avoided.
- In soldering, do not apply any stress to the lead frame particularly when heated.
- When forming a lead, make sure not to apply any stress inside the resin.
- Lead forming must be done before soldering.
- It is necessary to cut the lead frame at normal temperature.

### 3. Peak Forward Current:

Condition for is IFP pulse : At 1ms cycle, 50% duty, emitting 32kHz square wave signal.



use a wrist band or  
ent and machinery must be


## Infrared Emitting Diode Specification

- Commodity: Infrared emitting diode
- Intensity Bin Limits (At 50mA)

BIN CODE	Min.(mW/sr)	Max.( mW/sr)
16	40	56
17	56	78

**Note:** The Ie guarantee should be added  $\pm 15\%$  tolerance.

### Suggest IR Reflow Condition For Lead Free:



**Typical Electrical / Optical Characteristics Curves  
(25°C Ambient Temperature Unless Otherwise Noted)**

